

# LOWBOY LB55 PAVER HR

**TTP**  
**TRUCK  
TRAILER  
PROS**



## GENERAL SPECS

- Tare Weight : Approximately 25,000 lb.
- GVWR : 120,000 lb
- Main Beams : Wide flange I-Beam 18" deep.
- Cross Member : Fabricated steel
- Upper Coupler Assembly : 5/16" thick pick-up plate
- Fifth Wheel Height : 47.5 inches
- Mud Flaps : 24" x 24" black plastic, 4 hole mounting
- Electrical System : 12 volt, 7-way split pin receptacle plug,
- Grote lights
- Tail : Hydraulic operated tail

## DIMENSIONS

- Overall Width : 102 inches
- Overall Length : 53 feet
- Bed Height : 40 inches

## TAIL:

- Bigger section length : 96 inches
- Smaller section length : 51 inches
- Security lockout : Air actuated

**TTP**  
**TRAILERS**

## HYDRAULIC POWER SOURCE:

- Engine : Honda GX390
- Horse Power : 13 HP
- Fuel : Gasoline
- Starter : Electric and Manual
- Pump : 3600 psi
- Displacement : 0.4 cu in / rev
- Reservoir : Self Hydraulics Reservoir

## WINCH

- Maximun working pressure : 2030 psi
- Wire diameter : 10 mm
- Wire length : 78 feet

## LANDING GEAR

- Landing Gear : Two speed, square leg, 60,000 lb. lift capacity and 170,000 lb. static load capacity.
- Type : Double shaft
- Landing Gear Foot Group : 10" × 9.5" low profile sandshoe
- Crank Handle Location : Roadside

## LIGHTING

- Light Attachment : Flange mounted
- Light Type : LED

## BRAKES

- Drum : Steel outboard mounted
- Lubrication : Synthetic Grease
- Brake System Type : 2S1M
- Brake Chambers : 30/30

## WHEELS

- Rims : 8.25" × 22.5"
- Tire Size : 255/70R22.5

## AXLES

- Axle Type : 5" round, tapered, 77.5" long
- Axle Quantity : Three
- Axle Location : 134 inches from tail rear
- Kingpin Location : 18 inches from rear face of front bolster.

## SUSPENSION

- Suspension Type : Air Suspension

## FINISH

- Metal Preparation : Clean, dry steel and commercial blast cleaning
- Primer : Zinc-rich primer
- Topcoat : Urethane



Truck Trailer Pros  
(210) 760-0509

Info@TruckTrailerPros.com  
TruckTrailerPros.com