
COIL FLATBED



GENERAL SPECS

- Tare Weight : Approximately 15,900 lb.
- GVWR : 90,000 lb
- Floor : Wood at 1 1/2"
- Cross Member : Fabricated steel
- Upper Coupler Assembly : 5/16" thick pick-up plate
- Fifth Wheel Height : 48 inches
- Mud Flaps : 24" x 30" black plastic, 4 hole mounting
- Electrical System : 12 volt, 7-way split pin receptacle plug
- Wincher : 4" Slider Wincher System
- Coil space : 3 ft
- Tool box : One steel tool box on each side

DIMENSIONS

- Overall Width : 102 inches
- Overall Length : 53 feet
- Bed Height : 58 inches
- Coil Bed Height : 39 inches

LANDING GEAR

- Landing Gear : Two speed, square leg. 60,000 lb. lift capacity and 170,000 lb. static load capacity.
- Landing Gear Foot Group : 10" x 9.5" low profile sandshoe
- Crank Handle Location : Roadside





LIGHTING

- Light Attachment : Flange mounted
- Light Type : LED

BRAKES

- Drum : Steel outboard mounted
- Lubrication : Synthetic Grease
- Brake System Type : 4S2M
- Brake Chambers : 30/30

WHEELS

- Rims : 8.25" × 22.5"
- Tire Size : 11R22.5
- Hub Type : Steel

AXLES

- Axle Type : 5" round, tapered, 77.5" long
- Axle Quantity : Three
- Axle Centers : 60 inches
- Axle Location : 68 inches from rear
- Kingpin Location : 36 inches from rear face of front bolster.

SUSPENSION

- Suspension Type : Air Suspension

FINISH

- Metal Preparation : Clean, dry steel and commercial blast cleaning
- Primer : Zinc-rich primer
- Topcoat : Urethane

Truck Trailer Pros
(210) 760-0509

Info@TruckTrailerPros.com
TruckTrailerPros.com