


---

# SAND CHASSIS

Can carry (1) 10' ISO box,  
(1) 20' ISO container or  
(2) 8' ISO boxes



## GENERAL SPECS

- Tare Weight : Approximately 10,040 lb.
- GVWR : 62,000 lb
- Cross Member: I-beam
- Upper Coupler Assembly: 5/16" thick pick-up plate
- Fifth Wheel Height: 47 inches
- Mud Flaps: 24" x 24" black plastic, 4 hole mounting
- Electrical System: 12 volt, 7-way split pin receptacle plug
- Gooseneck Beams: Fabricated I-beam with high-tensile steel

## DIMENSIONS

- Overall Chassis Width : 96 inches (102" over axles)
- Overall Chassis Length: 40 feet
- Bed Height: 30 inches

## LANDING GEAR



- Landing Gear : Two speed, square leg. 60,000 lb. lift capacity and 170,000 lb. static load capacity.
- Landing Gear Foot Group : 10" x 9.5" low profile sandshoe
- Crank Handle Location : Roadside

## LIGHTING

- Light Attachment : Flange mounted
- Light Type : LED

**TTP**  
**TRUCK  
TRAILER  
PROS**

**TISA**  
**TRAILERS**



## BRAKES

- Drum : Steel outboard mounted
- Lubrication: Synthetic Grease
- Brake System Type : 2S1M
- Brake Chambers : 30/30



## WHEELS

- Rims : 8.25" × 22.5"
- Tire Size : 255/70R22.5
- Hub Type : Steel



## AXLES

- Axle Type: 5" round, tapered, 77.5" long
- Axle Quantity: Two
- Axle Centers: 51 inches
- Axle Location: 16 inches from rear
- Kingpin Location: 30 inches from rear face of front bolster.



## SUSPENSION

- Suspension Type : Air Suspension

## ADD-ONS

- Fenders: Aluminum, over rear tandems



## FINISH

- Metal Preparation : Clean, dry steel and commercial blast cleaning
- Primer : Zinc-rich primer
- Topcoat : Urethane

Truck Trailer Pros  
(210) 760-0509

Info@TruckTrailerPros.com  
TruckTrailerPros.com