

**H24+**  
HST



## SPECIFICATIONS

FEATURES	H24+ HST
<b>ENGINE</b>	
Engine Model	3 Cylinder Mitsubishi Engine
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Ci)	80,42
Rated RPM	2500
Max Torque	76.3Nm@2000
<b>TRANSMISSION</b>	
Drive	4WD
Forward/Reverse Controls	Twin Touch Pedals
Gearbox	HST (2 Range)
Transmission Type	Constant Mesh
Cruise Control	Yes
<b>BRAKES</b>	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
<b>PTO</b>	
PTO (RPM)	Rear - 540@2451 Mid PTO - 2100@2438
PTO Clutch	Wet Type
PTO Actuation	Button Operated
Steering	Power Steering
<b>HYDRAULICS</b>	
3 Point Linkages	CAT1N
3 Point Lifting Capacity@ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	3,98
<b>CAPACITY</b>	
Fuel Tank (Gal)	7
<b>DIMENSIONS &amp; WEIGHT (R 14 Tires)</b>	
Weight (lbs)	2530
Wheel Base (in)	61.8



FEATURES	H24+ HST
<b>TIRES</b>	
R14 (Standard)	25x8,50-14 R14T & 14-17,5 R14T
Industrial	23x8,50-12 & 33x15,5-16,5
Turf	23x8,50-12 & 33x15,5-16,5
Turf	25x8,50-14 & 13,6x16
Agri	6x12 & 8,3x20
Radial	6,5/80-12 & 280/70R18
Galaxy Pro	220/55 R12 & 280/70 R16

## LOADER TECHNICAL SPECIFICATION

Loader Model	HB24
MSL	MSL
Max Lifting Height at Pivot Point (in)	85
Clearance with Attachment Dump (in)	58
Reach at Maximum Height (in)	17
Reach at Bucket on Ground (in)	56
Max. Dump Angle (Deg.)	45
Attachment Rollback Angle (Deg.)	43
Digging Depth Below Grade (in)	5,9
Breakout Force at Pivot Point (Dig Position) (lbs)	1146
Bucket Width (in)	60