

S24 (9F+9R) SHUTTLE XL 24HP (SHUTTLE DRIVE)



SPECIFICATIONS

FEATURES	S24 Shuttle XL
ENGINE	
Engine Model	Mitsubishi S3L2
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Ci)	80.42
Rated RPM	2500
Torque	76,3 Nm @ 2000
TRANSMISSION	
Drive	4WD
Forward/Reverse Lever	Synchromesh Shuttle Lever on Dashboard
Gearbox	9+9
Transmission Type	Constant Mesh with Synchromesh Shuttle Transmission
Cruise Control	Yes
BRAKES	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
PTO	
PTO (RPM)	540/540E
PTO Actuation	Mechanical
Steering	Power Steering
HYDRAULICS	
3 Point Linkages	CAT-1N
3 Point Lifting Capacity @ ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	6,5
CAPACITY	
Fuel Tank (Gal)	5,8
DIMENSIONS & WEIGHT (AGRI TIRES)	
Weight (lbs)	2513
Wheel Base (in)	61,8
Total Length (in)	112,00



FEATURES	S24 Shuttle XL
TIRES	
Industrial	23x8,50-12 & 33x15,5-16,5
Turf 1	23x8,50-12 & 33x15,5-16,5
Turf 2	25x8,50-14 & 13,6x16
Agri 1	6x12 & 8,3x20
Agri 2	7x14 & 8,3x24
Radial Agri	6,5/80-12 & 280/70 R18
Galaxy Pro	220/55 R12 & 280/70 R16

LOADER TECHNICAL SPECIFICATION

Loader Model	XB24
NSL/MSL	MSL
Max Lifting Height at Pivot Point (in)	85
Clearance with Attachment Dump (in)	58
Reach at Maximum Height (in)	17
Reach at Bucket on Ground (in)	56
Max. Dump Angle (Deg.)	45
Attachment Rollback Angle (Deg.)	43
Digging Depth Below Grade (in)	5,9
Breakout Force at Pivot Point (Dig Position) (lbs)	1146