



Solis


**RUGGED. RELIABLE.
READY FOR ANYTHING.**

58 HP MANUAL DRIVE

ALL STANDARD FEATURES



**HYDRAULIC
REAR REMOTES**



**HIGH TORQUE & HIGH CAPACITY
FUEL-EFFICIENT ENGINE**



**MECHANICAL SELF
LEVELING LOADER WITH
2866 lbs LIFT CAPACITY
AT PIVOT**



**REAR LIFTING CAPACITY
OF 5511 lbs &
6613 lbs (OPTIONAL)**



**12F+12R SYNCHRO
SHUTTLE
TRANSMISSION**



**ENHANCED 3- POINT
LINKAGES WITH QUICK ATTACH
& TELESCOPIC TYPE OPTIONS**



**WIDER FLAT
PLATFORM FOR EASY
OPERATIONS**



**HIGH HYDRAULIC FLOW
WITH HYDRAULIC TOP LINK
AS OPTION**



**TWIN PROJECTOR HEADLAMPS
WITH 100% METAL HOOD**



**VERSATILE TIRE
OPTIONS**



58 HP
MANUAL DRIVE

Designed for versatility and performance, the **Solis S60 ROPS** is a tough, 58 HP utility tractor built for serious work.

With a powerful 3-cylinder engine, mechanical shuttle transmission, and 4WD, it's ready for mowing, tilling, baling, and heavy loader tasks. A 3,086 lb lift capacity, dual remotes, and a heavy-duty 3-point hitch make it a smart choice for livestock farms, hobby farms, and property owners who need a dependable, no-nonsense workhorse.

SOLISTRACTORUSA.COM

S60 SPECIFICATIONS

RUGGED.
RELIABLE.
READY FOR
ANYTHING.

Solis
SOLISTRACTORUSA.COM

FEATURES	S60
ENGINE	
ENGINE MODEL	CRDi
HP CATEGORY	58
NO. OF CYLINDERS	3
ASPIRATION	TCIC
CUBIC CAPACITY (CI)	186.73
RATED RPM	2000
MAX .TORQUE	184.40
AIR CLEANER	DRY TYPE
COLD START	UP TO -30 DEGREE CELSIUS (WITH BLOCK HEATER & PAN HEATER)
EXHAUST	DOWNDRAFT (UPDRAFT OPTIONAL)
TRANSMISSION	
DRIVE	SYNCHRO SHUTTLE
GEARBOX	12F + 12R
FRONT AXLE	4WD
PTO	
PTO (RPM)	540
PTO (ACTUATION)	MECHANICAL
STEERING	POWER STEERING
MAX PTO POWER	49 HP
HYDRAULICS	
3 POINT LINKAGE	CAT II
LIFTING CAPACITY (LBS)	5511, 6613 (OPTIONAL)
STAY BARS	FLOATING
AUXILIARY HYDRAULIC CIRCUIT	2SA / 2DA
HYDRUALIC FLOW (GPM)	19.5
LIFT RODS	ADJUSTABLE
DIMENSIONS	
WEIGHT (LBS)	6581
WHEEL BASE (IN)	87
TOTAL LENGTH WITH TPL (IN)	MAX 160.6, MIN 150
TOTAL WIDTH (IN)	76.2
HEIGHT (IN) UP TO ROPS	104
GROUND CLEARANCE (IN)	13 (FRONT AXLE)
CAPACITY	
FUEL TANK (GAL)	17.17



FEATURES	S60
TIRES	
INDUSTRIAL	F 12.5/80-18, R4 & R 19.5L-24
AGRICULTURE	F 9.5-24 8, PR & R 16.9-28 12, PR
AGRICULTURE	F 8.3-24 8, PR & R 14.9-28 12, PR
RADIAL	F 280/85, R24 & REAR 420/85 R30
RADIAL	F 320/70, R24 & REAR 420/85 R30
STD TIRE	12.5/80-18 R4 & 18.4X24-R4
BRAKES	
TYPE	OIL IMMERSED BRAKES
TYPE OF ACTUATION	MECHANICAL
PARKING BREAK	MECHANICAL
DIFFERENTIAL LOCK	MECHANICAL

LOADER SPECIFICATIONS

FEATURES	7300 MSL
MAX LIFTING HEIGHT AT PIVOT POINT (IN)	128.6
CLEARANCE W/ ATTACHMENT DUMP (IN)	95.39
REACH AT MAXIMUM HEIGHT (IN)	33.68
MAX. DUMP ANGLE (DEGREE)	62
ATTACHMENT ROLLBACK ANGLE (DEG.)	41
DIGGING DEPTH BELOW GRADE (IN)	7.55
BREAKOUT FORCE AT PIVOT POIN (DIG POSITION) (LBS)	4069.733
BUCKET WIDTH (IN)	72.6
LIFTING CAPACITY TO FULL HEIGHT AT PIVOT POINT (LBS)	2866

* Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.



INDUSTRY LEADING WARRANTY

The Solis H24+ comes with a 3-year full warranty and a 5-year powertrain warranty—one of the best in its class. It's reliable protection that shows Solis stands behind every tractor they build.

